

WIDE FORMAT LAMINATOR

RSC-1650C, RSC-1650H

Protect & Preserve



MODEL -RSC-1650H

Features & Benefits

- **Fast** - Laminates pressure sensitive film up to 65" wide at a rate of 16.4' per minute.
- **Quality**– Digital controls for temperature (RSC-1650H only) and speed help deliver a perfect finish.
- **Versatility** -Designed for mounting (up to .6"), laminating individual or multiple copies of posters prints, POP signs, training aids, rigid or flexible signage, inkjet, photo, floor graphics and much more.
- **Easy To Use** - Simple one button operation plus remote control and foot pedal allow hands-free operation.
- **Convenient**– High quality rollers allow cold lamination for heat sensitive applications.

CAS Solutions

pauls@cassolutions.com

www.cassolutions.com

8751 162nd Lane NW
Ramsey, MN55303

Tel: (800) 248.4246 (763) 274-1119
Fax: (763) 274-0131

Royal Sovereign International, Inc.

Specifications for RSC-1650C, RSC-1650H

MODEL	RSC-1650C 65"	RSC-1650H 65"
Cold Lamination	√	√
Reverse Feature	√	√
Soft Touch Key Pad	√	√
Digital Speed Control	√	√
Digital Temperature Control		√
Mounting up to .6"	√	√
Remote Control & Foot Switch	√	√
Cross Cutter	√	√
Core Size	Includes 3" & 2 1/4" adapters	

Model	RSC-1650C	RSC-1650H
UPC	0 35565 77435	0 35565 77434 9 6
Unit Weight	551 (lbs) 250 (kg)	551 (lbs) 250(kg)
Unit Dimensions	77.2 x 25.6 x 47.6 (in) 1960 x 650 x 1210 (mm)	77.2 x 25.6 x 47.6 (in) 1960 x 650 x 1210 (mm)
Carton Weight	706 (lbs) 320 (kg)	706 (lbs) 320 (kg)
Carton Dimensions	84.7 x 35 x 51.9 (in) 2150 x 888 x 1318 (mm)	84.7x 35 x 51.9 (in) 2150 x 888 x 1318 (mm)
Power Requirements	AC 100~120V/50-60Hz/15 Amp	
Power Consumption	150W	1650W
Safety Features	Emergency stop button and safety guard	