

RSH-1151/1651



WIDE FORMAT DUAL HOT & COLD LAMINATORS



Features & Benefits

- **Fast** - Laminates pressure sensitive and thermal films up to 45" (1150mm) (RSH-1151) and 65" (1650mm) (RSH-1651) wide at speeds up to 9.8' (3m/min) per minute for hot lamination and 13' (4m/min) per minute for cold lamination.
- **Quality**– Digital controls for temperature and speed help deliver a perfect finish, combined with silicone rubber rollers.
- **Versatility** -Designed for mounting, laminating & encapsulating individual or multiple copies of posters prints, POP signs, training aids, rigid or flexible signage floor graphics, trade show displays and much more.
- **Convenient**– Auto-grip film shafts for easy material handling. High quality rollers allow cold lamination for heat sensitive applications.



CAS Solutions
www.cassolutions.com

763.274.1119 • 877.632.6406

8751 - 162nd Lane NW • Ramsey, MN 55303-3408

Royal Sovereign International, Inc.

Specifications

Model	RSH-1151	RSH-1651
Power supply	AC 200-240V/50-60Hz Single phase	AC 200-240V/50-60Hz Single phase
Power consumption	3300W	3300W
Film thickness	1-10 (mil) / 25-250 (mic)	1-10 (mil) / 25-250 (mic)
Max laminating width	45 (in) / 1150 (mm)	65 (in) / 1650 (mm)
Max laminating speed	Hot - 9.8 (ft/min) / 3 (m/min) Cold -13 (ft./min) / 4 (m/min)	Hot - 9.8 (ft/min) / 3 (m/min) Cold -13 (ft./min) / 4 (m/min)
Ready time	22 min	40 min
Heating method	Hot roller (internal infrared heater)	Hot roller
Driving motor	DC geared motor	DC geared motor
Temperature control	Digital up to 320°F (160°C)	Digital up to 320°F (160°C)
Speed control	Digital (micom)	Digital (micom)
Cooling system	2 Blower	3 Blower
Auto off/Standby	Yes	Yes
Cross cutter	Yes	Yes
Side cutter	Option	Option
Hot lamination	Yes	Yes
Cold lamination	Yes	Yes
Mounting/foam board	Yes/up to 5/8" (15mm)	Yes/up to 5/8" (15mm)
Paper counter	Yes	Yes
Length measurement	Yes	Yes
Reverse	Yes	Yes
Remote control	Yes	Yes
Foot pedal	Yes	Yes
Unit Weight	373 (lbs) / 169 (kg)	593 (lbs) / 269 (kg)
Unit Dimensions (W x D x H)	59 x 25.5 x 47.5 (in) 1500 x 650 x 1210 (mm)	77 x 25.5 x 47.5 (in) 1960 x 650 x 1210 (mm)
Carton Weight	618 (lbs) / 280 (kg)	869 (lbs) / 394 (kg)
Carton Dimensions (W x D x H)	65.5 x 35.5 x 57.5 (in) 1660 x 900 x 1460 (mm)	86 x 35.5 x 57.5 (in) 2190 x 900 x 1460 (mm)
Warranty	1 year parts & labor (Rollers 6 months)	1 year parts & labor (Rollers 6 months)