

WIDE FORMAT LAMINATOR

RSH-1050, RSH-1650

Protect & Preserve



Features & Benefits

- **Fast** - Laminates pressure sensitive and thermal film up to 65" wide at a rate of 6.6' per minute.
- **Quality**– Digital controls for temperature and speed help deliver a perfect finish.
- **Versatility** -Designed for mounting, laminating & encapsulating individual or multiple copies of posters prints, POP signs, training aids, rigid or flexible signage floor graphics, trade show displays and much more.
- **Easy To Use** - Simple one button operation and remote control with foot pedal allow hands-free operation.
- **Convenient**- Nine job memory setting feature for frequently used settings.

CAS Solutions

pauls@cassolutions.com

www.cassolutions.com

8751 162nd Lane NW
Ramsey, MN 55303

Toll-Free: 888.413.4744 **Phone:** 763.241.7441

Fax: 763.274.0131

Royal Sovereign International, Inc.

Specifications for RSH-1050, RSH-1650

MODEL	RSH-1050 41.3"	RSH-1650 65"
Hot & Cold Lamination	√	√
Reverse Feature	√	√
Soft Touch Key Pad	√	√
Digital Speed & Temp. Control	√	√
9 Storable Memory Functions	√	√
Mounting up to .6"	√	√
LCD Display	√	√
Remote Control & Foot Pedal	√	√
Paper Count & Length Measurement	√	√
Cross Cutter	√	√
Cooling Fans	√	√
Core Size	Includes 3" & 2 1/4" adapters	

Model	RSH-1050	RSH-1650
UPC	0 3556577424 0	0 3556573632 3
Unit Weight	375 (lbs) 170 (kg)	706 (lbs) 320 (kg)
Unit Dimensions	55.1 x 25.6 x 47.4 (in) 1400 x 650 x 1210 (mm)	77.2 x 25.6 x 47.4 (in) 1960 x 650 x 1210 (mm)
Carton Weight	529 (lbs) 240 (kg)	860 (lbs) 390 (kg)
Carton Dimensions	61 x 34.9 x 51.8 (in) 1550 x 888 x 1318 (mm)	84.5 x 34.9 x 51.8 (in) 2150 x 888 x 1318 (mm)
Power Requirement	AC 200~220V/60Hz /15 Amp/single phase	
Power Consumption	3000W	3500W
Safety Features	Emergency stop button and safety guard with lock-out switch	